

# Copex-eco

## All-round stripper

- ▲ Active cleaning, low-foaming stripper
- ▲ Preferably used for alkali-sensitive resilient floorings
- ▲ Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- ▲ Free from butyl glycol
- ▲ Does not require CLP Regulation markings



### Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

### Application

Please test on a small inconspicuous spot before first application.

#### Polymer stripping:

1–3 L to 8 L of cold water.

Distribute the cleaning solution on the floor, leave to react for approx. 15–20 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m<sup>2</sup>.



### Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

### Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, water-soluble solvents, solubilizers.  
pH value (concentrate): approx. 9.5

pH value (ready-to-use solution): approx. 9

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j150910	10 L canister	60