

# Thermodur ESD

## Conductive all-purpose emulsion polish

- ▲ Self-shining polymer emulsion
- ▲ Outstanding film-forming properties
- ▲ Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- ▲ Very good water resistance
- ▲ Resistant to surface disinfectant products
- ▲ Fulfills the requirement to DIN ICE EN 61340-5-1 (TÜV Süd material test certificate)
- ▲ Tested to EN 1081



### Area of application

Can be used on water-resistant, coatable, stripped, conductive and dissipative floorings, such as PVC, rubber, linoleum and synthetic resins. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

### Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

### Coating (conductive floorings):

Depending on the absorbency of the surface, 1–2 layers at intervals of approx. 45 minutes.

Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer.

Consumption: 25.0 ml/m<sup>2</sup> per application.



### Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

### Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, resins, softeners, preservatives.  
pH value (concentrate): approx. 8.5