



Application method

Dry cleaning (parquet)

Dry cleaning removes maintenance films and dirt from wood and parquet surfaces without damaging the floor due to moisture.



Step 1: Preparation

Stack furniture where necessary. Sweep or use a damp cloth (gauze cloth) to remove coarse, loose dirt.



Step 2: Set-up the machine

Fit the rotary floor machine with vacuum attachment and suction ring. Affix additional weight if required.



Step 3: Use a machine on the floor area

Move the machine with a Kiehl-Legno-Pad over the floor in spiral, overlapping strokes until the embedded dirt has been removed and the floor has an even, matt finish. If necessary, turn over the Kiehl-Legno-Pad or replace it with a new pad.



The safety advice and instructions for use on the containers, the product information and the safety data sheet must be observed. Please also observe the cleaning and maintenance recommendations of the manufacturers as well as the instruction manual of the machines and equipment used.



Application method

Dry cleaning (parquet)



Step 4: Clean the edges

Edges, corners, rims and other areas inaccessible to the machine need to be manually treated using a hand pad and an edge-cleaning device. Stubborn encrusted dirt may need to be removed with a spatula.



Step 5: Dust removal

Thoroughly vacuum the cleaned area with a vacuum cleaner or use a damp cloth to remove the dust.



Step 6: Clean the devices

Rinse the rotary floor machine, industrial vacuum cleaner, etc. and clean inside and out with a cloth. Clean the cable with a cloth and check for damage.

