

104 Idropul

Cleaner for high-pressure units and self-service jet washes

- ▲ Very high cleaning performance when faced with road dirt, insects, organic contaminants and brake abrasion
- ▲ Outstanding at dissolving statically adhesive dirt
- ▲ Offers a very good protection of the vehicle and car wash equipment
- ▲ Particularly environmentally aware and gentle composition
- ▲ Highly economical thanks to the very strong product concentration
- ▲ Free from EDTA, NTA, phosphates and fragrances



Application

Only use on alkali-resistant surfaces (e.g. undamaged, coated aluminium rims). Prior to use, see instructions provided by the material and surface manufacturer and check for material compatibility where required. Do not apply on hot surfaces.

Product is suitable for pre-dilution

Apply either undiluted or prediluted to the application with a suitable dosing device. The shelf life of diluted solutions is reduced by the storage conditions and water quality. Also suitable for the use by end consumers if they have been given sufficient instructions.

Pre- and intensive cleaner:

In low-pressure systems as a spray application (car ≥ 1:60; truck ≥ 1:20; bus ≥ 1:20).

In high-pressure systems as a spray application (10–20 ml/min).

Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. In case of high water temperatures (> 40 °C) and/or water hardness (> 4.5 mmol/L ≈ 25 °dH), adding "316 Calciel" may be sensible to avoid the formation of limescale. Apply extensively to saturate the surface. Do not allow the cleaning solution to dry. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Anionic surfactants < 5%, alkalis, complexing agents, corrosion protection.
pH value (concentrate): approx. 13

Classification

Classification (in concentrate): GHS07, Warning. H319 Causes serious eye irritation. H315 Causes skin irritation. P280 Wear protective gloves/eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

| Art. No. | Packaging unit (PU) | Contents in kg | Numbers of PU per pallet |
|----------|---------------------|----------------|--------------------------|
| c104025 | 25 kg canister | | 24 |
| c104073 | 220 L drum | 239 | 2 |