

# 109 BiFuTec JetFoam

# Powerful cleaning foam for self-service jet washes

- Very high cleaning performance when faced with road dirt, insects, organic contaminants and brake abrasion
- Very good at dissolving statically adhesive dirt
- ▲ Offers a very good protection of the vehicle and car wash equipment
- Very dense and fine-pored foam which adheres extremely well when used in foam devices
- Particularly effective when used in a KIEHL-BiFuTec foam system or with the KIEHL-BiFuTec foam lance
- Creates a pleasant and intensely fragrant atmosphere at the washing bay and within the washing hall
- Particularly environmentally aware and gentle composition
- Very economical thanks to maximised product concentration
- Free from EDTA, NTA and phosphates







## **Application**

Only use on alkali-resistant surfaces (e.g. undamaged, coated aluminium rims). Prior to use, see instructions provided by the material and surface manufacturer and check for material compatibility where required. Do not applicate on hot surfaces.

#### Product is suitable for pre-dilution

Apply either undiluted or prediluted to the application with a suitable dosing device. The shelf life of diluted solutions is reduced by the storage conditions and water quality. Also suitable for the use by end consumers if they have been given sufficient instructions.

#### Pre- and intensive cleaner:

In high-pressure systems as a foam application (20 ml/min).

Optimised for the operation with KIEHL-BiFuTec foam lances; more product is likely to be consumed when other lances are used.

#### Foam:

In self-service jet washes as brush foam (8-16 ml/min).

In automatic car washes as active foam (4-9 ml/car).

#### Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. In case of high water temperatures (> 40 °C) and/or water hardness (> 4.5 mmol/L  $\approx$  25 °dH), adding "316 Calciel" may be sensible to avoid the formation of limescale. Apply extensively to saturate the surface. Do not allow the cleaning solution to dry. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

### Ingredients (according to 648/2004/EC)

Anionic surfactants 5–15%, alkalis, complexing agents, water-soluble solvents, additives, corrosion protection, fragrances (Limonene). pH value (concentrate): approx. 13

#### Classification

Classification (in concentrate): GHS05, Danger. H318 Causes serious eye damage. H315 Causes skin irritation. P280 Wear protective gloves/eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Contains: Sodium Laureth Sulfate / Sodium Hydroxide (INCI)

Art. No.	Packaging unit (PU)	Contents in kg	Numbers of PU per pallet
c109025	25 kg canister		24
c109073	220 L drum	245	2

12.02.2024 Page 1 of 1