



142 ENERGY Prewash balance

Low foaming alkaline intensive cleaner, unperfumed

- Maximum cleaning performance when faced with road dirt, insects, organic contaminants and brake abrasion
- Outstanding at dissolving statically adhesive dirt
- ▲ Does not damage uncoated concrete floors unlike acidic products
- Ensures optimum recycling water qualities and high rates of water recycling
- Designed to be low-foaming, in order to avoid excessive foam in the basin system
- Contains renewable plant-based raw materials
- Energy-saving due to reduced aeration requirements in water recycling
- ▲ Environmentally aware and gentle composition
- Very economical thanks to maximised product concentration
- Free from EDTA, NTA, phosphates and fragrances













Application

Only use on alkali-resistant surfaces (e.g. undamaged, coated aluminium rims). Prior to use, see instructions provided by the material and surface manufacturer and check for material compatibility where required. Do not applicate on hot surfaces.

Product is suitable for pre-dilution

Apply either undiluted or prediluted to the application with a suitable dosing device. The shelf life of diluted solutions is reduced by the storage conditions and water quality. Only approved for proper use by trained personnel.

Pre- and intensive cleaner:

In low- or high-pressure systems as a spray application (car \geq 1:80; truck \geq 1:25; rim \geq 1:10).

Shampoo

In automatic car washes as brush shampoo (3–5 ml/m commercial vehicle length).

Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. In case of high water temperatures (> 40 °C) and/or water hardness (> 4.5 mmol/L \approx 25 °dH), adding "316 Calciel" may be sensible to avoid the formation of limescale. Apply extensively to saturate the surface. Do not allow the cleaning solution to dry. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, phosphonates < 5%, alkalis, additives, dyes. pH value (concentrate): approx. 13.5

Classification

Classification (in concentrate): GHS05, Danger. H314 Causes severe skin burns and eye damage. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Contains: Sodium Hydroxide (INCI)

 Art. No.
 Packaging unit (PU)
 Contents in kg
 Numbers of PU per pallet

 c142025
 25 kg canister
 24

 c142073
 220 L drum
 256
 2

12.02.2024 Page 1 of 1