

201 Automotive Dry

Drying agent

- ▲ Quick and extensive break-up of the water film
- ▲ Good drying results with minimal residual water
- ▲ Achieves a water and dirt-repellent effect
- ▲ Can also be used within critical fresh water quality (e.g. water hardness)
- ▲ Ideal for convertible soft top canvas
- ▲ Extremely environmentally aware and gentle composition
- ▲ Economical to use thanks to the very high content of active ingredients in the concentrate
- ▲ Free of hydrocarbons, mineral oils and fragrances
- ▲ Free of silicones



Application

Product is not suitable for pre-dilution

Apply undiluted to the application with a suitable dosing device.

Drying agent:

In car washes with blower drying as a spray application (15–30 ml/car).

Apply extensively over the vehicle.

In car washes with no blower drying as a spray application (4–7 ml/min; 1:1000–2000).

Apply extensively over the vehicle. As to produce a delayed break-up of the water film, it is important to use a high dilution.

Note

Always keep containers closed and guide suction tubes through the closure. Protect from frost. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! No liability is accepted in case of incorrect and unprofessional use!

Ingredients

Cationic compounds, maintenance substances, water-soluble solvents, solubilizers, dyes.
pH value (concentrate): approx. 4.5

Art. No.	Packaging unit (PU)	Contents in kg	Numbers of PU per pallet
c201025	25 kg canister		24
c201073	220 L drum	217	2
c201090	1000 L container	985	1