

# 242 Rocura

## Tyre maintenance and rim sealing

- ▲ Gives excellent colour depth and produces a silky matt gloss finish on tyres and plastic parts
- ▲ Impregnating effect ensuring good water and dirt repellency
- ▲ Particularly environmentally aware and gentle composition
- ▲ Extremely economical thanks to the maximum content of active ingredient in the superconcentrate
- ▲ Free of hydrocarbons, mineral oils and fragrances



### Application

#### Product is suitable for pre-dilution

Apply either undiluted or pre-diluted to the application with a suitable dosing device using a ratio of 1+9 or use manually. The shelf life of diluted solutions is reduced by the storage conditions and water quality.

#### Wax and care:

In mechanical tyre and wheel care units as a spray application (20–40 ml/car).

In a manual process as a care for tyres and plastic (20–40 ml/car).

Apply with a brush or sponge, or spray on.

Do not overdose, as excess product can reach unwanted surfaces while driving.

#### Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. No liability is accepted in case of incorrect and unprofessional use!

#### Ingredients

Maintenance substances, emulsifiers.

pH value (concentrate): approx. 7

#### Classification

Classification (in concentrate): GHS07, Warning. H319 Causes serious eye irritation. P280 Wear eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

Art. No.

c242025

Packaging unit (PU)

25 kg canister

Numbers of PU per pallet

24