

# 261 AirDry

## Drain drying agent for units without blower

- ▲ Produces a closed rinsing water film
- ▲ Reduces residual water and therefore avoids residues and marks on treated surfaces
- ▲ Ideal in combination with osmosis water rinsing
- ▲ A high ratio of surfactants also achieves a great cleaning effect
- ▲ Economical to use thanks to the very high content of active ingredients in the concentrate
- ▲ Free of hydrocarbons, mineral oils and fragrances
- ▲ Free of silicones



### Application

#### Product is suitable for pre-dilution

Apply either undiluted or pre-diluted to the application with a suitable dosing device using a ratio of 1:2. The shelf life of pre-diluted solutions is reduced by the storage conditions and water quality.

#### Drying agent:

In car washes with no blower drying as a spray application (4–10 ml/m vehicle length).

In a manual process as a flush application (1:200–400).

Apply extensively over the vehicle.

#### Shampoo:

In car washes with no blower drying as brush shampoo (10–30 ml/min; 4–10 ml/m vehicle length; 1:500–1500).

When using recycled water, fresh water must be used for rinsing.

#### Note

Always keep containers closed and guide suction tubes through the closure. Protect from frost. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! No liability is accepted in case of incorrect and unprofessional use!

#### Ingredients (according to 648/2004/EC)

Anionic surfactants < 5%, additives, dyes, preservatives (Sodium Pyrithione, Benzisothiazolinone).  
pH value (concentrate): approx. 2

Art. No.	Packaging unit (PU)	Contents in kg	Numbers of PU per pallet
c261025	25 kg canister		24
c261073	220 L drum	221	2
c261090	1000 L container	1005	1