

301 Clarofloc

High-performance flocculant

- ▲ Cleans neutral to alkaline wastewater and recycled water
- ▲ Very rapid flocculation
- ▲ Causes very compact sedimentation
- ▲ Considerably reduces both clouding and the CSB and BSB value
- ▲ Effective across a very broad range of pH values
- ▲ Also highly effective at low temperatures
- ▲ Highly economical thanks to the very strong product concentration
- ▲ Free from complexing agents and phosphates



Application

Product is not suitable for pre-dilution

Apply undiluted to the application with a suitable dosing device.

Water treatment:

In systems with water recycling as intensive treatment (60–100 ml/m³ recycling water).

Add to all sedimentation tanks.

as on-going treatment (60–100 ml/m³ resulting slop; 10–30 ml/car).

Feed the water inlet to the 1st sedimentation tank and ensure it is well-mixed.

Optimum effect at pH 7.5 - 8.0.

Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients

Flocculating agent.

pH value (concentrate): approx. 3

Classification

Classification (in concentrate): GHS05, Warning. H290 May be corrosive to metals. H319 Causes serious eye irritation. P280 Wear eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
c301025	25 kg canister	24