

316 Calciel

Limescale protection for high-pressure cleaning machines

- ▲ Effectively prevents the formation of limescale on the walls and surfaces of containers and heating aggregates
- ▲ Protects the membranes when creating osmosis water
- ▲ Significantly reduces the deterioration of high-pressure nozzles in hard water areas
- ▲ Increases the compatibility of detergents in the case of high water hardness levels and/or high temperatures
- ▲ Protects the material on the surfaces in question
- ▲ Highly economical thanks to the very strong product concentration
- ▲ Free from EDTA, NTA and phosphates



Application

Product is suitable for pre-dilution

Apply either undiluted or pre-diluted to the application with a suitable dosing device using a ratio of 1:2. The shelf life of diluted solutions is reduced by the storage conditions and water quality.

As protection against calcification:

In reverse osmosis systems

approx. 1 ml per 0.2 mmol/l and per m³ water flow.

In high-pressure applications

When adding without impulse generator, approx. 6 ml per 0.2 mmol/l and per m³ water flow. If no dosing device is available, a direct addition of 5-10 % to the detergents is possible.

Note

Always keep containers closed and guide suction tubes through the closure. The plant manufacturer's instructions must be adhered to. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients

Dispersing agents, sequestering agents.

pH value (concentrate): approx. 6

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
c316029	10 kg canister	60
c316073	220 L drum	2