

Li-Ex

Special stripper

- ▲ Active cleaning, low-foaming stripper
- ▲ Preferably used for alkali-sensitive resilient floorings
- ▲ Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- ▲ Free from butyl glycol



Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:

1–3 L to 8 L of cold water.

Distribute the cleaning solution on the floor, leave to react for approx. 10 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, soap < 5%, complexing agents, water-soluble solvents, dyes, fragrances (Limonene).

pH value (concentrate): approx. 9.5

pH value (ready-to-use solution): approx. 9

Classification

Classification (in concentrate): GHS07, Warning. H315 Causes skin irritation. H319 Causes serious eye irritation. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

| Art. No. | Packaging unit (PU) | Numbers of PU per pallet |
|----------|---------------------|--------------------------|
| j150210 | 10 L canister | 60 |
| j150272 | 200 L drum | 2 |