

Poly-Ex

Powerful stripper

- ▲ Active cleaning, low-foaming stripper
- ▲ For alkali-resistant floorings
- ▲ Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- ▲ Highly alkaline
- ▲ Contains renewable plant-based raw materials



Area of application

Can be used on water and alkali-resistant floorings, such as PVC, granite, porcelain stoneware tiles. Not suitable for use on linoleum and rubber floors or on calcite-based stones such as marble or terrazzo tiles.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:

1–3 L to 8 L of cold water.

Distribute the cleaning solution on the floor, leave to react for approx. 10 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, soap < 5%, alkalis, water-soluble solvents, fragrances.

pH value (concentrate): approx. 13

pH value (ready-to-use solution): approx. 12

Classification

Classification (in concentrate): GHS05, GHS07, Danger. H335 May cause respiratory irritation. H314 Causes severe skin burns and eye damage. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Contains: Ethanolamine / Trideceth 5-12 / Potassium Hydroxide (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j150310	10 L canister	60
j150372	200 L drum	2