

Li-Ex-eco

Special stripper

- ▲ Active cleaning, low-foaming stripper
- ▲ Preferably used for alkali-sensitive resilient floorings
- ▲ Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- ▲ Free from butyl glycol
- ▲ Awarded with the Austrian Ecolabel
- ▲ Contains renewable plant-based raw materials



Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:

1–3 L to 8 L of cold water.

Distribute the cleaning solution on the floor, leave to react for approx. 10–15 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, soap < 5%, water-soluble solvents.

pH value (concentrate): approx. 9.5

pH value (ready-to-use solution): approx. 9

Classification

Classification (in concentrate): GHS07, Warning. H319 Causes serious eye irritation. P280 Wear eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j151005	Carton of 2 x 5 L PCR canisters	56
j151072	200 L drum	2