

Thermodur-schwarz

All-purpose emulsion polish for asphalt floors

- ▲ Self-shining polymer emulsion
- ▲ Outstanding film-forming properties
- ▲ Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- ▲ Very good water resistance



Area of application

Can be used on water-resistant, stripped black industrial floorings, e.g. asphalt tiles.

Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying. Shake well before use.

Coating:

Depending on the absorbency of the surface, 2–3 layers at intervals of approx. 30 minutes. Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer. Consumption: 25.0 ml/m² per application.

An additional layer of Thermodur (colourless, Art. No. j200205) must be applied to prevent mechanical abrasion of the black coloured particles.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, resins, softeners, dyes, preservatives.
pH value (concentrate): approx. 8.5

| Art. No. | Packaging unit (PU) | Numbers of PU per pallet |
|----------|---------------------|--------------------------|
| j205310 | 10 L canister | 60 |