

# Prisma Steinprotektor

## Stone protector

- ▲ Outstanding film-forming properties
- ▲ Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- ▲ Polishing (approx. 1000 rpm) produces a high-gloss, hard-wearing maintenance film that is safe to walk on
- ▲ Easy removal of scuff marks by polishing (approx. 1000 rpm)
- ▲ Top stripping without use of a stripper, as part of the intensive cleaning



### Area of application

For use on absorbent natural and artificial stone floorings such as marble, granite, terrazzo tiles and Travertine. Not suitable for porcelain tiles and high-gloss stone surfaces.

### Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

#### Coating:

Depending on the absorbency of the surface, 2–3 layers at intervals of approx. 30 minutes. Following stripping or intensive cleaning and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer. The dried maintenance layer must be compacted by polishing (approx. 1000 rpm, Multi-Disc). Consumption: 25.0 ml/m<sup>2</sup> per application.

#### Spray buffing for restoring damaged parts of the coating:

Dilute product 1:1 with cold water.

Apply using a spray bottle and polishing machine (approx. 1000 rpm). Consumption: 1.0 ml/m<sup>2</sup>.

#### Polishing:

Occasional polishing (approx. 1000 rpm) compacts the care components, removes scuff marks caused by traffic and increases durability.

Applying excessively thick layers increases scuff marks.



#### Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

#### Ingredients

Synthetic dispersions, waxes, emulsifiers, additives, softeners, preservatives.  
pH value (concentrate): approx. 8.5