

Kiehl-Parketta

Superior-quality liquid hard wax

- ▲ High-quality solvent-based wax
- ▲ Prevents the swelling of water-sensitive floorings
- ▲ Prevents water from penetrating the treated surface
- ▲ Easy to use



Area of application

For applying wax to untreated and to waxed, oiled-waxed and sealed-waxed real wood indoor surfaces. Can also be used on Cotto floorings.

Application

Wax coating:

Depending on the absorbency of the surface, 1–3 layers at intervals of approx. 60 minutes. Use product undiluted. Pour product onto the cleaned floor and immediately spread thinly using a flat mop or waxer. Consumption: 80.0–150.0 ml/m² per application.

Wax maintenance:

Depending on the desired care effect 1–2 layers at intervals of approx. 60 minutes. Use product undiluted. Consumption: 20.0–40.0 ml/m² per application.

Spray buffing on prewaxed surfaces:

Only use product with explosion-proof machinery! Dilute Kiehl-Parketta with Kiehl-Wax-Ex at a ratio of 1:1 and pour into the spray can. Spray a small amount on soiled areas or scuff marks and immediately polish to a shine. Turn soiled red pad or replace with a clean pad.

Polishing:

The wax film dries with a matt finish and must be polished with a polishing machine (150–1000 rpm, polishing brush or polishing pad) to make it shine.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost. Do not allow to get into wastewater. Not miscible with water! Do not smoke!

Ingredients

Hard waxes, water-insoluble solvents, fragrances.

Classification

Classification (in concentrate): GHS02, GHS07, GHS08, Danger. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. P271 Use only outdoors or in a well-ventilated area. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P370+P378 In case of fire: Use extinguishing powder to extinguish. EUH066 Repeated exposure may cause skin dryness or cracking. Contains: C10-12 Alkane / Cycloalkane (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j220170	Carton of 2 x 5 L tin canisters	76