

# Server

## Filling system for scrubber driers

- ▲ For the quick filling of cleaning machines with ready-to-use solutions
- ▲ Tank filled with water only, i.e. no germs, no odours and fresh cleaning solution at all times
- ▲ Made of resistant, robust plastic
- ▲ Can be transported with a pallet truck or forklift
- ▲ System separator via free outlet in accordance with DIN EN 1717



### Application

Water connection with max. 5 bar pressure. Never plug the plug directly into the socket, always plug it in via a RCD!

### Technical data

Product variant	Server 180	Server 250
Dimensions [cm] (W x H x D):	100 x 85 x 67	110 x 100 x 85
Weight [kg]:	25	30
Water connection:	3/4" external thread	3/4" external thread
Water pressure max. [bar]:	5	5
Water temperature max. [°C]:	40	40
Power connection:	230 V / 50 Hz 16 A	230 V / 50 Hz 16 A
Filling quantity [L]:	180	250
Dosing range [%]:	0,29 - 7	0,29 - 7
Filling rate Server [L/min]:	16	16
Filling rate cleaning machine [L/min]:	45	45
Safety:	RCD personal circuit breaker, DVGW: Unobstructed outlet according to DIN 1717:2000	RCD personal circuit breaker, DVGW: Unobstructed outlet according to DIN 1717:2000

### Accessories

Designation	Art. No.	Packaging unit (PU)	Description
	z123142	1	7 dosing nozzles
Injector	z123140	1	Injector for Server
Pump	z123110	1	Pump with backflow preventer

Art. No.  
auf Anfrage  
z123026

Description  
Server 180  
Server 250

Packaging unit (PU)  
1  
1