

according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier 128 XMAX Prefoam UFI EDA0-E092-Y00M-VSWU 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Product for professional cleaning and maintenance 1.3. Details of the supplier of the safety data sheet Company name: KAW KIEHL KG Street: Oskar-von-Miller-Str. 1 Place: D-85235 Odelzhausen +49 8134 9305-40 Telefax: +49 8134 5145 Telephone: e-mail: info@kiehl-group.com Contact person: Laboratory department www.kiehl-group.com Internet: Responsible Department: Notrufnummer für deutsch- und englischsprachige Länder: +49/89/19240 Vergiftungsinformationszentrale (VIZ) Österreich: +43 1 406 43 43 Nationale Notrufnummer für die Schweiz (Tox-Zentrum Zürich): 145 Numéro d'urgence France: INRS: +33 (0) 1 45 42 59 59 Numero d' emergenza Italia: Centro Antiveleni - 20162 Milano: 02/66101029 ETTSZ /Egészségügyi Toxikológiai Tájékoztató Szolgálat/, 1096 Budapest, Nagyvárad tér 2. Ügyeleti telefonszám: +36 80 201-199 Emergency telephone number for all other countries: +49/8134/9305-169 **KIEHL Austria GmbH** Perfektastr. 57; A-1230 Wien Tel. +43 (0) 1 / 604 99 93 **KIEHL FRANCE S.A.R.L.** 5. rue de Londres: F-67670 Mommenheim Tél. +33 (0) 3.88.59.52.25 KIEHL Italia s.r.l. Via San Rocco, 101; I-16036 Recco (GE) Tel. +39 / 0185 730 008 **KIEHL Schweiz AG** St. Dionys-Str. 33; CH-8645 Jona Tel. +41 (0) 55 / 254 74 74 KIEHL Hungary Kft. Felsöipari körút 3/ D HU-2142 Nagytarcsa Tel. +36 (0) 1 / 348-08 41 **KIEHL Middle East LLC** A8-LIU 48/49 - KIZAD Abu Dhabi, U.A.E. Tel. +971 2 550 33 96 1.4. Emergency telephone +49/89/19240 (germanophone and anglophone)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Corr. 1B; H314

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Sodium Hydroxide

Signal word:

Pictograms:





according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 2 of 9

Hazard statements

H314

Causes severe skin burns and eye damage.

Precautionary statements

| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if |
| | present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| | |

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

according to 648/2004/CE: nonionic surfactants <5%, anionic surfactants 5-15%, phosphonates <5%, alkalis, complexing agents, solubilizers, corrosion inhibitors, dyes, perfumes (Linalool, Limonene)

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|---|--------------|------------------|------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation |) | | |
| 68439-57-6 | Olefinsulfonate-Na-salt | | | 5 - < 10 % |
| | 270-407-8 | | 01-2119513401-57 | |
| | Skin Irrit. 2, Eye Dam. 1; H315 H3 [.] | | | |
| 97489-15-1 | Sodium C14-17 Sec Alkyl Sulfonat | 1 - < 5 % | | |
| | 307-055-2 | | 01-2119489924-20 | |
| | Acute Tox. 4, Skin Irrit. 2, Eye Dan | | | |
| 1310-73-2 | Sodium hydroxide | | | 1 - < 5 % |
| | 215-185-5 | 011-002-00-6 | 02-2119752469-26 | |
| | Skin Corr. 1A; H314 | | | |

Full text of H and EUH statements: see section 16.

| Specific Conc. Limits, M-factors and ATE | | | | |
|--|--|---------------------------|------------|--|
| CAS No | EC No Chemical name | | | |
| | Specific Conc. | Limits, M-factors and ATE | | |
| 68439-57-6 | 270-407-8 | Olefinsulfonate-Na-salt | 5 - < 10 % | |
| | Skin Irrit. 2; H315: >= 5 - 100 Eye Dam. 1; H318: >= 38 - 100 Eye Irrit. 2; H319: >= 5 - < 38 | | | |
| 97489-15-1 | 9-15-1 307-055-2 Sodium C14-17 Sec Alkyl Sulfonate | | | |
| | oral: ATE = 500 mg/kg_Skin Irrit. 2; H315: >= 10 - 100_Eye Dam. 1; H318: >= 15 - 100_Eye Irrit. 2; H319: >= 10 - < 15 | | | |
| 1310-73-2 | 215-185-5 Sodium hydroxide 1 - < | | | |
| | Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2 | | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Avoid contact with skin and eyes.

After inhalation

not hazardous by inhalation



according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 3 of 9

After contact with skin

Wash off immediately with soap and plenty of water. Take off all contaminated clothing immediately.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

This information is not available.

4.3. Indication of any immediate medical attention and special treatment needed

Show this safety data sheet to the doctor in attendance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Any extinguishing means and measures are acceptable.

5.2. Special hazards arising from the substance or mixture

This information is not available.

5.3. Advice for firefighters

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product itself does not burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Avoid contact with skin, eyes and clothing.

For non-emergency personnel

Use personal protection equipment.

For emergency responders

Use personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Wipe up with absorbent material (e.g. cloth, fleece).

Clean contaminated articles and floor according to the environmental legislation.

Other information

Never return spills in original containers for re-use.

6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling



according to UK REACH Regulation

128 XMAX Prefoam Product code: c1280 sd

Revision date: 12.12.2022

Advice on safe handling

Avoid contact with skin and eyes.

Advice on protection against fire and explosion No special protective measures against fire required.

Advice on general occupational hygiene

General industrial hygiene practice.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store at room temperature in the original container. Store in a place accessible by authorized persons only.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Do not store near acids.

Further information on storage conditions

Keep container tightly closed.

Never return unused material to storage receptacle.

7.3. Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|-----------|------------------|-----|-------|-----------|---------------|--------|
| 1310-73-2 | Sodium hydroxide | - | 2 | | STEL (15 min) | WEL |

8.2. Exposure controls

Appropriate engineering controls

Not required.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166

Hand protection

Protective gloves

Recommendation: Nitrile gloves with a coating thickness of 0.4 mm which protect at least 8 hours (corresponds to the permeability level 6 of the European norm DIN/EN 374) and provide a resistance to swelling of < 15%.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Not required

Environmental exposure controls

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | liquid |
|-----------------|----------------|
| Colour: | green |
| Odour: | characteristic |

Revision No: 1,02

Page 4 of 9



according to UK REACH Regulation

| 128 XMAX Prefoam | | | | |
|---|----------------------------------|-------------|--|--|
| Revision date: 12.12.2022 | Product code: c1280_sd | Page 5 of 9 | | |
| Melting point/freezing point: Boiling point or initial boiling point and boiling range: | <0 °C >98 °C | | | |
| Flammability Solid/liquid: | not applicable | | | |
| Lower explosion limits: | not applicable | | | |
| Upper explosion limits: | not applicable | | | |
| Flash point: | >100 °C | | | |
| Auto-ignition temperature: | not applicable | | | |
| Decomposition temperature: | not determined | | | |
| pH-Value (at 20 °C): | | K-QP1012C | | |
| Viscosity / kinematic: | not determined | | | |
| Water solubility: (at 20 °C) | completely miscible | | | |
| Solubility in other solvents | | | | |
| not determined | not determined | | | |
| Partition coefficient n-octanol/water: Vapour pressure: | not determined not determined | | | |
| Density (at 20 °C): | | K-QP1012E | | |
| Relative vapour density: | not determined | | | |
| 9.2. Other information | | | | |
| | | | | |
| Information with regard to physical hazard cla Explosive properties | asses | | | |
| Not explosive | | | | |
| Self-ignition temperature Solid: | not applicable | | | |
| Gas: | not applicable | | | |
| Oxidizing properties Not relevant | | | | |
| Other safety characteristics | | | | |
| Evaporation rate: | not determined | | | |
| Solid content: | not determined | | | |
| Sublimation point: | not applicable | | | |
| Softening point: | not applicable | | | |
| Pour point: | not applicable | | | |
| Viscosity / dynamic: | not determined | | | |
| Flow time: | not determined | | | |
| | | | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This information is not available.

10.2. Chemical stability

This information is not available.

10.3. Possibility of hazardous reactions

This information is not available.

10.4. Conditions to avoid

Do not expose to temperatures above 35 °C.

10.5. Incompatible materials

This information is not available.



according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 6 of 9

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

Further information

Do not mix with other detergents or chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|------------|-----------------------------------|------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 97489-15-1 | Sodium C14-17 Sec Alkyl Sulfonate | | | | |
| | oral | ATE 500 mg/kg | | | |

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This information is not available.

Further information

Health injuries are not known or expected under normal use.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. The surfactants in the product meet all requirements of the detergents regulation 648/2004/EC. Readily biodegradable, according to appropriate OECD test.

12.3. Bioaccumulative potential

This information is not available.

12.4. Mobility in soil

This information is not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties



according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 7 of 9

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

This information is not available.

Further information

Chemical Oxygen Demand (COD): 466mg O2/g

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose of waste into sewer.

List of Wastes Code - residues/unused products

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

List of Wastes Code - used product

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Clean container with water. Return cleaned containers to the company for recycling. Offer rinsed packaging material to local recycling facilities.

SECTION 14: Transport information

Land transport (ADR/RID)

| <u>14.1. UN number or ID number:</u> | UN 1824 |
|---|--------------------------------------|
| 14.2. UN proper shipping name: | SODIUM HYDROXIDE SOLUTION |
| <u>14.3. Transport hazard class(es):</u> | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| | |
| Classification code: | C5 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 80 |
| Tunnel restriction code: | E |
| Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> | UN 1824 SODIUM HYDROXIDE SOLUTION |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: Hazard label: | 8 |
| | ° |
| Classification code: | C5 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |



according to UK REACH Regulation

| Revision date: 12.12.2022 Marine transport (IMDG) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: | Product code: c1280_sd UN 1824 SODIUM HYDROXIDE, SOLUTION 8 III 8 | Page 8 of 9 | | |
|---|---|-------------|--|--|
| <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> | SODIUM HYDROXIDE, SOLUTION 8 III | | | |
| | 8 | | | |
| Special Provisions: Limited quantity: Excepted quantity: EmS: Segregation group: | 223 5 L E1 F-A, S-B alkalis | | | |
| 14.5. Environmental hazards | | | | |
| ENVIRONMENTALLY HAZARDOUS: | No | | | |
| 14.6. Special precautions for user Not required 14.7. Maritime transport in bulk according to not applicable | o IMO instruments | | | |
| SECTION 15: Regulatory information | | | | |
| 15.1 Safety health and environmental regul | ations/legislation specific for the substance or mixture | | | |
| EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 75 | | | | |
| National regulatory information | | | | |
| Water hazard class (D): 2 - obviously hazardous to water | | | | |
| 15.2. Chemical safety assessment | | | | |
| - | tances in this mixture were not carried out. | | | |
| SECTION 16: Other information | | | | |
| Abbreviations and acronyms ADR: Accord européen sur le transport | the previous version in section(s): 3 / 6 / 7 / 8 / 12 des marchandises dangereuses par Route nternational Carriage of Dangerous Goods by Road) | | | |

CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN: United Nations



according to UK REACH Regulation

128 XMAX Prefoam

Revision date: 12.12.2022

Product code: c1280_sd

Page 9 of 9

DNFL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) EmS: Emergency Schedules MFAG: Medical First Aid Guide MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure | | |
|---------------------|--|--|--|
| Skin Corr. 1B; H314 | | Calculation method | |
| Relevant H and EU | H statements | (number and full text) | |
| H302 | Harmfu | Harmful if swallowed. | |
| H314 | Cause | Causes severe skin burns and eye damage. | |
| H315 | Causes skin irritation. | | |
| H318 | Causes serious eye damage. | | |
| H412 | Harmful to aquatic life with long lasting effects. | | |

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)