

according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

419 XMAX Foma Plus

UFI: PEF0-60QR-C00V-YU9V

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Product for professional cleaning and maintenance

1.3. Details of the supplier of the safety data sheet

Company name: KAW KIEHL KG
Street: Oskar-von-Miller-Str. 1
Place: D-85235 Odelzhausen

Telephone: +49 8134 9305-40 Telefax: +49 8134 5145

e-mail: info@kiehl-group.com
Contact person: Laboratory department
Internet: www.kiehl-group.com

Responsible Department: Notrufnummer für deutsch- und englischsprachige Länder: +49/89/19240

Vergiftungsinformationszentrale (VIZ) Österreich: +43 1 406 43 43 Nationale Notrufnummer für die Schweiz (Tox-Zentrum Zürich): 145

Numéro d'urgence France: INRS: +33 (0) 1 45 42 59 59

Numero d' emergenza Italia: Centro Antiveleni - 20162 Milano: 02/66101029 ETTSZ /Egészségügyi Toxikológiai Tájékoztató Szolgálat/, 1096 Budapest,

Nagyvárad tér 2. Ügyeleti telefonszám: +36 80 201-199

Emergency telephone number for all other countries: +49/8134/9305-169

KIEHL Austria GmbH Perfektastr. 57; A-1230 Wien Tel. +43 (0) 1 / 604 99 93 KIEHL FRANCE S.A.R.L. 5. rue de Londres: F-67670 Mommenheim Tél. +33 (0) 3.88.59.52.25 KIEHL Italia s.r.l. Via San Rocco, 101; I-16036 Recco (GE) Tel. +39 / 0185 730 008 KIEHL Schweiz AG St. Dionys-Str. 33; CH-8645 Jona Tel. +41 (0) 55 / 254 74 74 KIEHL Hungary Kft. Felsőipari körút 3/ D HU-2142 Nagytarcsa Tel. +36 (0) 1 / 348-08 41 KIEHL Middle East LLC A8-LIU 48/49 - KIZAD Abu Dhabi, U.A.E. Tel. +971 2 550 33 96

1.4. Emergency telephone

+49/89/19240 (germanophone and anglophone)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Corr. 1B; H314

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Sodium Hydroxide

Signal word: Danger

Pictograms:





according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 2 of 9

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

according to 648/2004/CE: nonionic surfactants <5%, anionic surfactants 5-15%, EDTA 5-15%, phosphonates <5%, alkalis, solubilizers, corrosion inhibitors, dyes

Hazardous components

| CAS No | Chemical name | | | | |
|------------|---|--------------|------------------|--|--|
| | EC No | Index No | REACH No | | |
| | Classification (GB CLP Regulation) | | | | |
| 64-02-8 | tetrasodium ethylene diamine tetraacetate | | | | |
| | 200-573-9 | 607-428-00-2 | 01-2119486762-27 | | |
| | Acute Tox. 4, Acute Tox. 4, Eye Dam. 1, STOT RE 2; H332 H302 H318 H373 | | | | |
| 68439-57-6 | Olefinsulfonate-Na-salt | | 5 - < 10 % | | |
| | 270-407-8 | | 01-2119513401-57 | | |
| | Skin Irrit. 2, Eye Dam. 1; H315 H31 | | | | |
| 1310-73-2 | Sodium hydroxide | | 1 - < 5 % | | |
| | 215-185-5 | 011-002-00-6 | 02-2119752469-26 | | |
| | Skin Corr. 1A; H314 | | | | |
| 97489-15-1 | Sodium C14-17 Sec Alkyl Sulfonate | | 1 - < 5 % | | |
| | 307-055-2 | | 01-2119489924-20 | | |
| | Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H302 H315 H318 H412 | | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | | |
|------------|-------------------------------------|---|------------|--|--|
| | Specific Conc. | Specific Conc. Limits, M-factors and ATE | | | |
| 64-02-8 | 200-573-9 | tetrasodium ethylene diamine tetraacetate | 5 - < 10 % | | |
| | inhalation: ATI mg/kg | E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500 | | | |
| 68439-57-6 | 270-407-8 | Olefinsulfonate-Na-salt | 5 - < 10 % | | |
| | Skin Irrit. 2; H3 | 15: >= 5 - 100 Eye Dam. 1; H318: >= 38 - 100 Eye Irrit. 2; H319: >= 5 - < 38 | | | |
| 1310-73-2 | 215-185-5 | Sodium hydroxide | 1 - < 5 % | | |
| | · · | H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < H319: >= 0,5 - < 2 | | | |
| 97489-15-1 | 307-055-2 | Sodium C14-17 Sec Alkyl Sulfonate | 1 - < 5 % | | |
| | oral: ATE = 50 Irrit. 2; H319: > | 0 mg/kg Skin Irrit. 2; H315: >= 10 - 100 Eye Dam. 1; H318: >= 15 - 100 Eye = 10 - < 15 | | | |





according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 3 of 9

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Avoid contact with skin and eyes.

After inhalation

not hazardous by inhalation

After contact with skin

Wash off immediately with soap and plenty of water. Take off all contaminated clothing immediately.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids.

If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting.

If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

This information is not available.

4.3. Indication of any immediate medical attention and special treatment needed

Show this safety data sheet to the doctor in attendance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Any extinguishing means and measures are acceptable.

5.2. Special hazards arising from the substance or mixture

This information is not available.

5.3. Advice for firefighters

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product itself does not burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Avoid contact with skin, eyes and clothing.

For non-emergency personnel

Use personal protection equipment.

For emergency responders

Use personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Wipe up with absorbent material (e.g. cloth, fleece).

Clean contaminated articles and floor according to the environmental legislation.





according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 4 of 9

Other information

Never return spills in original containers for re-use.

6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

No special protective measures against fire required.

Advice on general occupational hygiene

General industrial hygiene practice.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store at room temperature in the original container. Store in a place accessible by authorized persons only.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Do not store near acids.

Further information on storage conditions

Keep container tightly closed.

Never return unused material to storage receptacle.

7.3. Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|-----------|------------------|-----|-------|-----------|---------------|--------|
| 1310-73-2 | Sodium hydroxide | - | 2 | | STEL (15 min) | WEL |

8.2. Exposure controls

Appropriate engineering controls

Not required.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166

Hand protection

Protective gloves

Recommendation: Nitrile gloves with a coating thickness of 0.4 mm which protect at least 8 hours (corresponds to the permeability level 6 of the European norm DIN/EN 374) and provide a resistance to swelling of < 15%.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Not required

Environmental exposure controls

Handle in accordance with good industrial hygiene and safety practice.



according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: orange-red
Odour: characteristic

Test method

Melting point/freezing point: <0 °C
Boiling point or initial boiling point and >98 °C

boiling range:

Flammability

Solid/liquid: not applicable
Lower explosion limits: not applicable
Upper explosion limits: not applicable
Flash point: >100 °C
Auto-ignition temperature: not applicable
Decomposition temperature: not determined

pH-Value (at 20 °C): > 13,5 K-QP1012C

Viscosity / kinematic: not determined
Water solubility: completely miscible

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 1,19 g/cm³ K-QP1012E

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
Not explosive
Self-ignition temperature

Solid: not applicable Gas: not applicable

Oxidizing properties Not relevant

Other safety characteristics

Evaporation rate:

Solid content:

Sublimation point:

Softening point:

Pour point:

Viscosity / dynamic:

Not determined

not applicable

not applicable

not applicable

not applicable

not applicable

not determined

not determined

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

This information is not available.

10.2. Chemical stability

This information is not available.



according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 6 of 9

10.3. Possibility of hazardous reactions

This information is not available.

10.4. Conditions to avoid

Do not expose to temperatures above 35 °C.

10.5. Incompatible materials

This information is not available.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

Further information

Do not mix with other detergents or chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|------------|---|--------------|----------|---------|--------|--------|
| | Exposure route | Dose | | Species | Source | Method |
| 64-02-8 | tetrasodium ethylene diamine tetraacetate | | | | | |
| | | ATE mg/kg | 500 | | | |
| | inhalation vapour | ATE | 11 mg/l | | | |
| | inhalation dust/mist | ATE | 1,5 mg/l | | | |
| 97489-15-1 | Sodium C14-17 Sec Alkyl Sulfonate | | | | | |
| | | ATE mg/kg | 500 | | | |

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This information is not available.

Further information

Health injuries are not known or expected under normal use.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 7 of 9

12.2. Persistence and degradability

The surfactants in the product meet all requirements of the detergents regulation 648/2004/EC.

12.3. Bioaccumulative potential

This information is not available.

12.4. Mobility in soil

This information is not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

This information is not available.

Further information

Chemical Oxygen Demand (COD): 502mg O2/g

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose of waste into sewer.

List of Wastes Code - residues/unused products

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease,

soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

List of Wastes Code - used product

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease,

soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Clean container with water. Return cleaned containers to the company for recycling.

Offer rinsed packaging material to local recycling facilities.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C5
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION



according to UK REACH Regulation

419 XMAX Foma PlusRevision date: 12.12.2022Product code: c4190_sdPage 8 of 9

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C5
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-B
Segregation group: alkalis

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Not required

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3 / 6 / 7 / 8 / 12

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association



according to UK REACH Regulation

419 XMAX Foma Plus

Revision date: 12.12.2022 Product code: c4190_sd Page 9 of 9

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|---------------------|--------------------------|
| Skin Corr. 1B; H314 | Calculation method |

Relevant H and EUH statements (number and full text)

| H302 | Harmful if swallowed. |
|------|---|
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H332 | Harmful if inhaled. |
| H373 | May cause damage to organs (Respiratory system) through prolonged or repeated |
| | exposure if inhaled. |
| H412 | Harmful to aquatic life with long lasting effects. |

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)